



Very Well Connected™

INSTALLATION INSTRUCTIONS

Product

7160-0325, 7160-0372

VISOR MOUNT, 1 UNIT, SINGLE SIDE ATTACHMENT

Revision

Rev.D

Form

INST-520

Printing Spec: PS-001

The Visor Mount, 1 Unit, Single Side Attachment provides the user with the capability to secure a mobile camera to the passenger side visor. Each system includes one Max³ all axis knuckle that allows the user to orient the camera in several positions. In addition, the system is equipped with two rubber pads and several mounting holes to ensure the camera is held secure and firm.

Tools Needed

5/64-in Hex wrench (Allen wrench)

3/16-in Hex wrench (Allen wrench)

Material Needed

#10 Self drilling screw

#8 x 1.00 sheet metal screw for 2010+ Charger

Installation

1. Remove the passenger side visor retainer clip near the center of the vehicle. Refer to figure 1.
2. Secure the Visor Mount to the headliner using the visor retainer and two additional self tapping fasteners.
 - a. Self tapping fasteners are not supplied.
 - b. **Caution: Self tapping fasteners that are too long may go through roof of vehicle.**
3. Secure the camera to the front camera bracket using (2) ¼-20 x .50 socket button head cap screw, (2) ¼-in lock washer, and (4) ¼-in nylon flat washers. Refer to figure 2.
4. Position the camera as desired.
5. Insert one and tighten (2) #10-32 socket head set screws to lock the Max³ knuckle in place. Refer to figure 2.



Figure 1. Secure Visor Mount with passenger side visor retainer.




Figure 2: Assemble camera with 1/4-in fasteners

Product Mounting Disclaimer

Gamber-Johnson is not liable under any theory of contract or tort law for any loss, damage, personal injury, special, incidental or consequential damages for personal injury or other damage of any nature arising directly or indirectly as a result of the improper installation or use of its products in vehicle or any other application. In order to safely install and use Gamber-Johnson products full consideration of vehicle occupants, vehicle systems (i.e., the location of fuel lines, brakes lines, electrical, drive train or other systems), air-bags and other safety equipment is required. Gamber-Johnson specifically disclaims any responsibility for the improper use or installation of its products not consistent with the original vehicle manufactures specifications and recommendations, Gamber-Johnson product instruction sheets, or workmanship standards as endorsed through the Gamber-Johnson Certified Installer Program.

© copyright 2011 Gamber-Johnson, LLC

If you need assistance or have questions, call Gamber-Johnson at 1-800-456-6868