

Testing Summary

Slim FZ-G1 Family of Docking Stations and Cradles

(7160-0595-XX, 7160-0759)

Summary of Tests Performed at Gamber-Johnson

Test Description	Test Parameters
Vibration – Operational Test date: June 2015	MIL-STD-810G, Method 514.6, Procedure 1, Category 4, per Figure 514.6C-1. Test duration is one hour along three mutually orthogonal axes – not simultaneously (3 hours total). <ul style="list-style-type: none"> • Unit is unlocked • Panasonic provided operating conditions
Vibration – Operational RF Connection Test date: June 2015	MIL-STD-810G, Method 514.6, Procedure 1, Category 4, per Figure 514.6C-1. Test duration is one hour along three mutually orthogonal axes – not simultaneously (3 hours total). <ul style="list-style-type: none"> • Unit is unlocked • Panasonic provided operating conditions • Test is performed simultaneously with operational test. • Test is monitored to record any breaks in RF connectivity during vibration.
Vibration – Non-Operational (Minimum Integrity) Test date: June 2015	MIL-STD-810G, Method 514.6, Category 24, per Figure 514.6E-1. Test duration is one hour along three mutually orthogonal axes – not simultaneously. <ul style="list-style-type: none"> • Unit is unlocked • Panasonic provided operating conditions
Vibration – Non-Operational Sinusoidal Test date: June 2015	10-200Hz Sine Sweep <ul style="list-style-type: none"> • Panasonic provided operating conditions
Functional Shock - Non-Operational Test date: June 2015	MIL-STD-810G, Method 516.6, Procedure 1, 3 positive and 3 negative pulses each axis (vertical, longitudinal and transverse), 18 pulses <ul style="list-style-type: none"> • 20G, 11ms half sine • Unit is unlocked
Mechanical Shock Safety - Non-Operational Test date: June 2015	MIL-STD-810G, Method 516.6, Procedure 1, 3 positive and 3 negative pulses each axis (vertical, longitudinal and transverse), 18 pulses <ul style="list-style-type: none"> • 40G, 11ms half sine • Unit is unlocked
Cycle Testing – Non-Operational Test date: July 2015	10,000 cycles of the docking connector, latching and locking mechanisms

An ISO 9001:2008 certified company

Electrostatic Discharge – Operational Test date: July 2015	ISO 10605, Section 8, Table C.2, Category 2 – Direct Air Discharge
---	--

Summary of Tests Performed at Independent Facility

Shock – Crash Hazard Test date: June 2015	SAE J1455, Section 4.11.3.5, per Figure 13 <ul style="list-style-type: none"> • Unit is unlocked
Head Strike Performance Test Test date: July 2015	ADR 21/00
EMC Testing Test date: July 2013 Test Data (7160-0486)	EN 55022:2010/AC:2010 <ul style="list-style-type: none"> • CISPR 22 – Class B • FCC Part 15, Subpart B – Class B
EMC Testing Test date: July 2013 Test Data (7160-0486)	UN ECER Regulation No. 10 (E-Mark)
Safety Testing Test date: July 2016 Test Data (7160-0486)	60950 <ul style="list-style-type: none"> • IEC 60950-1(ed. 2);am1;am2 • EN60950-1:2006/A2:2013 • CAN/CSA C22.2 No. 60950-1:2007/A2:2014-10 • UL 60950-1:2007/R:2014-10
EMC Testing Test date: Sept 2013 Test Data (7160-0486)	EN 50498 <ul style="list-style-type: none"> • 2010 Electromagnetic Compatibility (EMC)

Other Certifications

Description
EN 50581:2012 RoHS2 Directive 2011/65/EU

An ISO 9001:2008 certified company