

INSTALLATION INSTRUCTIONS

Product 7160-1302

Revision
Rev.A

Form INST-868

PETERBILT 389 DASH MOUNT

Printing Spec:PS-001


This instruction sheet is for the Gamber-Johnson Peterbilt 389 dash mount. For other products sold by Gamber-Johnson please reference their specific instruction sheets.

The Peterbilt 389 dash mount is designed to mount to the dash where 2 spare switches are located side by side. You will need a Zirkona for Big Rigs mount to complete the solution.

Attaching the mount:

- 1. Remove cover strip and the steering wheel cover panel from the dash to expose the screws underneath. They are held in place with spring clips.
- 2. Remove the radio switch panel mounting screws and pull out the radio switch panel from the dash.
- 3. Remove 2 spare switches from the dash that are side by side. This will expose the 2 rectangular openings on the radio switch panel where the Peterbilt 389 dash mount can be attached.





Product Mounting Disclaimer

Gamber-Johnson is not liable under any theory of contract or tort law for any loss, damage, personal injury, special, incidental or consequential damages for personal injury or other damage of any nature arising directly or indirectly as a result of the improper installation or use of its products in vehicle or any other application. In order to safely install and use Gamber-Johnson products full consideration of vehicle occupants, vehicle systems (i.e., the location of fuel lines, brakes lines, electrical, drive train or other systems), air-bags and other safety equipment is required. Gamber-Johnson specifically disclaims any responsibility for the improper use or installation of its products not consistent with the original vehicle manufactures specifications and recommendations, Gamber-Johnson product instruction sheets, or workmanship standards as endorsed through the Gamber-Johnson Certified Installer Program.

Attaching the mount (continued):

- 4. To complete your solution you will need a Zirkona for Big Rigs mount. Attach the Zirkona mount to the Peterbilt 389 dash mount with the #10-32 hardware supplied with the Zirkona mount. Run the #10-32 screws with the lock washers though the round base plate on the Zirkona mount, then through the rectangular cover plate, through the switch plate openings in the radio switch panel and into the back plate that has the pressed in threaded fasteners.
- 5. With the mount attached to the radio switch panel, reattach the panel to the dash with the screws removed in step 2.
- 6. Reattach the steering wheel cover plate and the cover strip removed in step 1.
- 7. Attach the device being mounted to the Zirkona for Big Rigs mount using the hardware supplied with the device.

