



Testing Summary

Samsung Active II Tablet Full Docking Station

(7160-1005-00, 7160-1029-00)

Summary of Tests Performed at Gamber-Johnson

Test Description	Test Parameters
Vibration – Operational Test date: Dec., 2017	MIL-STD-810G, Method 514.6, Procedure 1, Category 4, per Figure 514.6C-1. Test duration is one hour along three mutually orthogonal axes – not simultaneously (3 hours total). <ul style="list-style-type: none"> Unit is unlocked
Vibration – Non-Operational (Minimum Integrity) Test date: Dec., 2017	MIL-STD-810G, Method 514.6, Category 24, per Figure 514.6E-1. Test duration is one hour along three mutually orthogonal axes – not simultaneously. <ul style="list-style-type: none"> Unit is unlocked
Functional Shock - Non-Operational Test date: Dec., 2017	MIL-STD-810G, Method 516.6, Procedure 1, 3 positive and 3 negative pulses each axis (vertical, longitudinal and transverse), 18 pulses <ul style="list-style-type: none"> 20G, 11ms half sine Unit is unlocked
Mechanical Shock Safety - Non-Operational Test date: Dec., 2017	MIL-STD-810G, Method 516.6, Procedure 1, 3 positive and 3 negative pulses each axis (vertical, longitudinal and transverse), 18 pulses <ul style="list-style-type: none"> 40G, 11ms half sine Unit is unlocked
Cycle Testing – Non-Operational Test date: Dec., 2017	30,000 cycles of the docking connector, latching and locking mechanisms
Electrostatic Discharge – Operational Test date: Dec., 2017	ISO 10605, Section 8, Table C.2, Category 2 – Direct Air Discharge

Summary of Tests Performed at Independent Facility

Test Description	Test Parameters
Humidity Test date: Dec., 2017	MIL-STD 810G, Method 507.5, Procedure II, Aggravated, Table 507.5-IX <ul style="list-style-type: none"> Ten 24-hour cycles, temperature varied from 30°C to 60°C to 30°C at constant 95% relative humidity.
Low Temperature: Operational Test date: Dec., 2017	MIL-STD 810G, Method 502.5, Procedure II <ul style="list-style-type: none"> -20°C Operating, 24-hour duration

An ISO 9001:2008 certified company

Gamber-Johnson LLC · 3001 Borham Avenue · Stevens Point, Wisconsin 54481
PHONE: 1-715-344-3790 · FAX: 1-715-344-5209 · EMAIL: gamberj@gamberjohnson.com ·
www.gamberjohnson.com



Low Temperature: Storage Test date: Dec., 2017	MIL-STD 810G, Method 502.5, Procedure I <ul style="list-style-type: none"> -40°C Non-Operating, 24-hour duration
High Temperature: Operational Test date: Dec., 2017	MIL-STD 810G, Method 501.5, Procedure II, Table 501.5-II, Induced Conditions <ul style="list-style-type: none"> Five 24-hour cycles, temperature varied from 30°C to 60°C to 30°C
High Temperature: Storage Test date Dec., 2017	MIL-STD 810G, Method 501.5, Procedure I, Table 502.5-III, Induced Conditions <ul style="list-style-type: none"> Seven 24-hour cycles, temperature varied from 33°C to 71°C to 33°C
Shock – Crash Hazard Test date: 6/5/2018	SAE J1455, Section 4.11.3.5, per Figure 13 <ul style="list-style-type: none"> Unit is unlocked
EMC Testing Test date: Dec., 2017	ECE R10: 2014 Addendum 9, Revision 5
EMC Testing Test date: Dec., 2017	EN 55032:2015 <ul style="list-style-type: none"> CISPR 32 – Class A FCC Part 15, Subpart B – Class A
Safety Testing Test date: Jan., 2018	60950 <ul style="list-style-type: none"> IEC 60950-1(ed. 2);am1;am2 EN60950-1:2006/A2:2013 CAN/CSA C22.2 No. 60950-1:2007/A2:2014-10 UL 60950-1:2007/R:2014-10

Other Certifications

Description
EN 50581:2012 RoHS2 Directive 2011/65/EU

An ISO 9001:2008 certified company