

AFS INSTALLER ADAPTABLE HARNESSES

These products are designed to offer a wide array of configurations and options. Installer Harnesses are designed to be used with a Power Prep Harness. Utilizing separate harnesses for the lighting installation allows the customer to scale the power distribution to their application.

ADAPTABLE DESIGN ARRAY:


Options that may be added to the Base IFL1 (7300-0057) Harness (may select none, one or all of the options)

ITEM NO.	DESCRIPTION	PLACEMENT	WEIGHT
7300-0059	Vehicle Sense, Right Spot Light, & Rebroadcast (A)	Right Spot Light	1.0 lb.
7300-0060	Sync Option, Provides Common Sync Wire at Each Lighthead (S)	Sync wire provided for all lighting wire options in the harness	1.0 lb.
7300-0061	2nd 100 Watt Siren Speaker, Wire Pair from Siren to Speaker (2)	Under hood to Switchbox location	1.0 lb.
7300-0062	Low Frequency Siren, 3 Wires from Siren to Speakers (L)	Under hood to Switchbox location	1.0 lb.
7300-0063	Warning Lights at European/Front Marker Light Locations (E)	Driver & Passenger	1.0 lb.
7300-0064	Side Mirror Warning Lights (M)	Driver & Passenger side	1.0 lb.
7300-0065	Mid-Ship Lights at the B or C Pillar (B)	Driver & Passenger side	1.0 lb.
7300-0066	Radio Power, 20 Amp, 10 Gauge (X)	Front Battery to Console	1.0 lb.
7300-0067	Radio Power, 20 Amp, 10 Gauge (Y)	Front Battery to Trunk Tray	1.0 lb.
7300-0068	Radio Power, 20 Amp, 10 Gauge (Z)	Rear Battery to Console	1.0 lb.
7300-0069	Radio Power, 20 Amp, 10 Gauge (W)	Rear Battery to Trunk Tray - Braided	1.0 lb.







AFS INSTALLER ADAPTABLE HARNESSES: WIRING CONFIGURATIONS




Shown: 7300-0060




Shown: 7300-0061 & 7300-0062




Shown: 7300-0063




Shown: 7300-0064




Shown: 7300-0065



Shown: 7300-0066



Shown: 7300-0067



Shown: 7300-0068